

## Perfect air pressure as you one needs

UNCALIBRATED  
BUT  
CALIBRATABLE








Our tyre inflation device **GATOR INFLATOR MID U** assures immediate operational availability and highest quality! No additional effort, no additional fees. Just pick it up and get started!

The tyre inflator complies with the harmonised European standard for tyre pressure gauges.

Type tested

Conformity tested

### TECHNICAL DATA:

 Weight	730 g
 Filling medium	air / nitrogen
 Max. permissible operating pressure	16 bar / 230 psi
 Pressure gauge measurement range	0 - 12 bar / 170 psi analogue pressure gauge
 Temperature range	-20°C to +55°C
 Pressure gauge display accuracy	pm ≤ 4 bar: ±0,08 bar 4 bar < pm ≤ 10 bar: ±0,16 bar pm > 10 bar: ±0,25 bar
 Pressure gauge graduation	0,1 bar / 2 psi

EVOLUTION OF AIR CONTROL

  
**ALLIGATOR®**



UNCALIBRATED  
BUT  
CALIBRATABLE

  
**ALLIGATOR®**

ALLIGATOR is a strong brand of WEGMANN automotive.

**WEGMANN automotive GmbH**  
Rudolf-Diesel-Straße 6  
97209 Veitshöchheim  
Germany

Phone: +49 (0) 931-32104-0  
E-Mail: [info@wegmann-automotive.com](mailto:info@wegmann-automotive.com)  
Internet: [www.wegmann-automotive.com](http://www.wegmann-automotive.com)

**GATOR INFLATOR MID U**

The uncalibrated filler for professionals

Article number: 9-149971

# FOR ALL PROFESSIONALS

Simple. Reliable. Multifunctional.

## SIMPLE

Due to the suspension eye, the device is always well placed and close at hand. With its flexible tube and the easy handling of the operating lever, tyre inflation is easier than ever before - even with one hand.

## RELIABLE

The **GATOR INFLATOR MID U** always delivers reliable measurement results. German Engineering.

## MULTIFUNCTIONAL

The measuring range of up to 16 bar makes the **GATOR INFLATOR MID U** a multifunctional device.



### Operation lever

made of metal for a easy handling even with one hand!

### Suspension eye

for simple and fast storage

### Ruber handle

non-slip rubber handle sheathed aluminium

### Valve adapter

Available for the use of moment plugs

### Quick coupling

(thread G3/8)

flexible use through variable plug nipples

### Compressed air hose

flexible rubber hose for an ergonomic working position  
Available length: 1,5 m