



# **ALLIGATOR CVV**<sub>EASY</sub> –

### A valve especially for commercial vehicles and mobile homes

In day-to-day operation, commercial vehicles and mobile homes are exposed to considerable pressures. The tire valve must seal reliably in different rims.



ALLIGATOR CVV<sub>EASY</sub> combines the pressure capacity of a metal valve with the easy mounting of a Snap-In rubber valve.

In the case of tyre pressures under 4.5 bar, special transporter valves are required.

## **Assembly**



Use mounting paste, press the valve in by hand.



Make sure the valve is sitting tightly in the rim.

## **Disassembly**





#### Recommendations for valve installation:

- ✓ Clean the rim flange and the area around the valve hole thoroughly. Check the valve hole area for damage.
- ✓ Before mounting, lubricate the valve with mounting paste or a similarly suitable lubricant.
- ✓ Replace the valve with a new quality valve from ALLIGATOR each time the tyres are changed.

No special tools necessary! No damage to rims!

ALLIGATOR Description	ALLIGATOR Artikel-No.
ALLIGATOR CVVeasy - 40 mm	530020
ALLIGATOR CVV <sub>EASY</sub> – 47 mm	530030
ALLIGATOR CVV <sub>EASY</sub> – 60 mm	530040

#### An overview of the advantages:

- ✓ Simple to mount by hand
- ✓ Reliable sealing in the rim up to 7 bar
- ✓ Easily removed without special tools
- ✓ No rim damage during disassembly
- ✓ High pressure capacity
- ✓ Fits almost every rim Valve hole must comply with the ETRTO standard





Patented thrust washer with predetermined breaking point.