



since
1920
valves
with reliability



ALLIGATOR Two-Wheelers

Safe and reliable

For your safeness: All Two-Wheeler valves with sealed valve cap and special valve core for motorbikes.

Valve hole \varnothing 8.3 +0.3 mm - Max. working pressure 14 bar

447413

25 MS SW 11
recommended installation
torque **7-10 Nm**
Nickel-plated brass



447513

34 MS SW 11
ETRTO V1.10.1 TR 430eq
recommended installation
torque **7-10 Nm**
Nickel-plated brass



447500

25 LMS
recommended installation
torque **4 ±0,5 Nm**
Aluminium



447505

25 LMS
recommended installation
torque **4 ±0,5 Nm**
Aluminium



Valve hole \varnothing 11.3 +0.4 mm

520944

Scooter rim valve 90°
max. speed 80 km/h



521548

Motorbike rim valve
TR412
ETRTO V2.03.6



447512

25 LMS
recommended installation
torque **4 ±0,5 Nm**
Aluminium



447515

25 LMS
recommended installation
torque **4 ±0,5 Nm**
Aluminium



Spare parts




Article No.	Description
	Plastic valve cap
300003	black with seal
300119	red with seal
300117	green with seal
300116	yellow with seal
300118	blue with seal
301500	Metall cap with seal
394930	Aluminium cap silver with seal
394934	Aluminium cap black with seal

valve core

315050 (left)
nickel-plated brass
for brass and aluminium valves

317200 (right)
messing brass
not for aluminium valves



characteristics

Opening pressure: **> 4,5 bar**
Temperature range: **-60 bis +200 °C**
Operating pressure: **< 20 bar**
Installation torque: **25 – 30 Ncm**

pictures
similar



ALLIGATOR Ventilfabrik GmbH
Richard-Steiff-Straße 4 | 89537 Giengen/Brenz

Fon: +49 (0) 73 22 · 130 · 1
Fax: +49 (0) 73 22 · 130 · 359

info@alligator-ventilfabrik.de
www.alligator-ventilfabrik.de

